

Lubricants - Engine Oil - Motorcycle Motor Oils

Version: 301/07

SynPower™ 2T Motorcycle Oil

Premium quality full synthetic motor oil for two-stroke motorcycle engines. Formulated for ultimate performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Performance levels

API: TC
JASO: FD
ISO: L-EGD

Applications

Pre-diluted for easier mixing and may be used in both injector and pre-mix applications.

Use fuel/oil ratios as specified by the engine manufacturer -- up to a maximum of 100:1.

Can be used in virtually all 2-stroke motorcycle engines including, 2-stroke injection systems and pre-mix systems.

Features & Benefits

Ultimate protection & performance

SynPower 2T engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading motorcycle engine manufacturers.

Wear protection

Provides ultimate protection against wear under all operating conditions. Designed to protect high performance engines.

Engine cleanliness

Keeps engine extremely clean by minimizing deposits.

Easy starts

Recommended for quick starting, even under very cold conditions or after long periods of engine inactivity.

Low smoke formulation

Specially formulated to produce minimal smoke.

Pre-diluted

Pre-diluted formulation for easy mixing.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

SynPower 2T	
Viscosity , mm ² /s @ 100 °C. ASTM D-445	10,4
Viscosity , mm ² /s @ 40 °C. ASTM D-445	62
Viscosity Index ASTM D-2270	157
Pour Point , °C ASTM D-5949	-45
Specific Gravity @ 15.6°C. ASTM D-4052	0,876
Flash Point , COC, °C. ASTM D-92	86

This information only applies to products manufactured in the following location(s): Europe

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 301/06

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.